

# HUMIDIFIERS ELECTRIC STEAM

GENERAL				DISTRIBUTOR				ELECTRICAL				NOTES
MARK	MFR.	MODEL	CAPACITY (LBS./HR.)	MODEL	ABSORPTION DISTANCE (FT.)	DUCT SIZE (EA.)	AIRFLOW (GPM) (EA.)	VOLTAGE	KW	FLA	MOCP	
HMD-1	NORTEC	NHTC-020	20	--	--	--	2,200	460/3/60	7.6	9.5	15	1
HMD-2	NORTEC	NHTC-075	75	21" Type MB	0.56	26x26	7,100	460/3/60	26.0	--	50	
HMD-3	NORTEC	NHTC-050	50	21" Type MB	0.56	26x24	5,850	460/3/60	17.2	21.5	35	
HMD-4	NORTEC	NHTC-030	30	17" Type MA	0.56	20x20	3,200	460/3/60	11.4	14.3	25	
HMD-5	NORTEC	NHTC-050	50	19" Type MB	0.56	26x22	5,700	460/3/60	17.2	21.5	35	
HMD-6	NORTEC	NHTC-020	20	15" Type MA	0.56	18x18	2,400	460/3/60	7.6	9.5	15	
HMD-7	NORTEC	NHTC-050	50	19" Type MB	0.56	22x22	4,300	460/3/60	17.2	21.5	35	

### ACCESSORIES

#### FURNISHED WITH UNIT (ALL UNITS) (FACTORY INSTALLED WHERE POSSIBLE):

1. DUCT MOUNTED HIGH LIMIT STAT
2. AIR PROVING SWITCH
3. 4-20 mA SINGLE CHANNEL DEMAND SIGNAL ACCEPTANCE:

### ACCESSORIES (CONT.)

#### FURNISHED BY OTHERS:

1. ROOM HUMIDISTAT BY T.C.C.
2. INTERLOCKING OF FACTORY ACCESSORIES BY T.C.C.
3. ELECTRIC DISCONNECT BY E.C.

### NOTES

1. HMD-1 TO BE PROVIDED WITH BLOWER PACK MOUNTED ON UNIT.